

# Birch

porcelain stoneware



**COBSA USA**

NEW YORK | NEW JERSEY | MIAMI



CENIZA

COPBICE830



| 8 x 30 |



СОПБИНА830



| 8 x 30 |



COPBINA830



| 8 x 30 |



COPBINO830



| 8 x 30 |



PEARL

COPBIPE830



| 8 x 30 |



TAUPE

COPBITA830



| 8 x 30 |

# Suggested Applications

Floor  Wall  Residential  Light Commercial  Heavy Commercial  Exterior  Pools

\*Wear can vary greatly. please consult with a professional.

# Installation Suggestions

**Plank Installation\***  **Modular Setting**  **Joint Size**  2mm

\*Install the offset the width of the plank. For professional installation, the use of leveling spacers for all plank and rectangular (ie. 12x24) format tiles is recommended.

**EDGE:**  Straight/Pressed  Rustic  Rectified

**FINISH:**  Matte  Polished  Structured  Honed  Semi-Polished

# Porcelain Type

through-body  color-bodied  glazed  unglazed  double-loaded  other

# Shade Variation

V1 Uniform Appearance  V2 Slight Variation  V3 Moderate Variation  V4 Substantial Variation

**THICKNESS:** 8mm **# OF FACES:** 30

# Slip Resistance

DCOF	Values	Applications
<input checked="" type="checkbox"/> .45	0.42	Recommended Standard DCOF value for wet/dry commercial flooring
	0.65	Recommended Standard DCOF value for ADA ramps

**DIN 51130** \*R9: Industry Standard/ADA Requirements \*\*R11: Recommended For Exteriors

R9\* (3-10°)  R10 (10-19°)  R11\*\* (19-27°)  R12 (27-35°)  R13 (>35°)

DIN 51097		
Class	Typical Applications	Critical Angle
<input type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, inclined pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

ASTM C-1028  
 ANSI A137.1  
 DIN 51097/51130

# Scratch Resistance

**MINERAL**

1. Talc (Talc)	6. Microline (Glass, Glazed Tile)
2. Gypsum (Fingernail)	7. Quartz (Unglazed Porcelain)
3. Calcite (Penny)	8. Topaz (Granite)
4. Flourite (Some Marbles)	9. Corundum (Ruby)
5. Apatite (Knife Blade)	10. Diamond (Diamond)

Industry standard ≤175mm<sup>2</sup>

MOH'S SCALE  
 UNI EN ISO 10545.6

**6**

# Wear Resistance

**PEI RATING**  
 UNI EN ISO 10545.7

Class 1: Walls only  
 Class 2: Residential floors w/minimal abrasive traffic  
 Class 3: Residential interiors/light commercial traffic  
 Class 4: Medium commercial applications  
 Class 5: All commercial applications/heavy traffic

\*Wear can vary greatly. please consult with a professional.

# Stain Resistance

5: Removed after 5 minutes (hot water running)  
 4: Removed by manual cleaning (weak detergent)  
 3: Removed by mechanical cleaning (strong detergent)  
 2: Removed by immersion (24 hrs in suitable solvent)  
 1: Stain not removed

ASTM C1378-04  
 UNI EN ISO 10545.14

**5**

# Water Absorption

ASTM C-373  
 UNI EN ISO 10545.3

	<input checked="" type="checkbox"/> Absorbs 0-.5%		<input type="checkbox"/> Absorbs .5-3%		<input type="checkbox"/> Absorbs 3-7%		<input type="checkbox"/> Absorbs 7% +
	<b>Impervious</b> Interior/Exterior Frost Resistant		<b>Vitreous</b> Interior/Exterior Frost Resistant		<b>Semi-Vitreous</b> Indoor Use Only		<b>Non-Vitreous</b> Indoor Use Only

# Breaking Strength

Industry standard should be greater than  
 250 lbs  
 or  
 50 N/MM<sup>2</sup>

ASTM C648  
 UNI EN ISO 10545.4

**PASS**

# Facial Dimension

ASTM c499-09  
 UNI EN ISO 10545.02

	Standard	Tolerance	Result
flatness	± 5mm	± .5%	<input type="checkbox"/>
thickness	± 6mm	± .5%	<input type="checkbox"/>
straightness	± 4.5mm	± .5%	<input type="checkbox"/>
squareness	± 5.4mm	± .6%	<input type="checkbox"/>
sides L/W	± 1.1mm ± 4.5mm	± .5%	<input type="checkbox"/>


# Chemical Resistance

ASTM C650  
 UNI EN ISO 10545.13

Allowances for:

	result
Acid	<input checked="" type="checkbox"/> A
Bases	<input checked="" type="checkbox"/> A
Chemicals	<input checked="" type="checkbox"/> A

# Leed Information



REQUIREMENTS FOR COMMERCIAL INTERIORS/NEW CONSTRUCTION

<b>Sustainable Sites</b> Site selection SS CREDIT 1 Heat Island Effect-non roof Material with a solar reflectant index of at least 29.	1 Point	<input checked="" type="checkbox"/>
<b>Energy &amp; Atmosphere</b> EA CREDIT 4 Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT	1 Point	<input checked="" type="checkbox"/>
<b>Indoor Environmental Quality</b> Low-Emitting Materials-Flooring Systems IEQ CREDIT 3.1-7 Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.	1 Point	<input type="checkbox"/>
IEQ CREDIT 4.1 Low Emitting Adhesives: Products less than 65 G/L VOC		<input type="checkbox"/>
IEQ CREDIT 4.3 Low Emitting Materials: Flooring systems.		<input type="checkbox"/>
<b>Materials &amp; Resources</b> M&R CREDIT 2 Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	1 Point	50% <input checked="" type="checkbox"/> 70% <input type="checkbox"/>
M&R CREDIT 4.1-4.2 Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.		10% <input type="checkbox"/> 20% <input checked="" type="checkbox"/>
M&R CREDIT 5 Regional Materials: Materials manufactured within 500 miles of the project site.		10% <input checked="" type="checkbox"/> 20% <input type="checkbox"/>
<b>Innovation in Design</b> ID CREDIT 1 Innovation in Design Measurable exemplary environmental performance.	1-5 Points	<input type="checkbox"/>

Type: **Porcelain Stoneware**  
 Product Line: **BIRCH**

\*The marketing name for this product is property of CobsA-USA. This same product may be marketed under different names.\*