





Cream



BELELCR1224



12x24



12x24 Deco

2x24 Bullnose



2x24 Listel



2x1 Mosaic



Grey



BELELGR1224



12x24

BELELGR1224E



12x24 Deco


BELEL GRBN 224



BELELGRLIS224



BELELGRMOS21







BELELIC1224



12x24

BELELIC1224D



12x24 Deco

RELELICRN22

2x24 Bullnose

BELELICLIS224



2x24 Listel

BELFLICMOS2



Product Specifications

Tile Thickness	5/16"
Minimum Grout Joint Recommendation	1/16"
Shade Variation	Low (V1)

D.C.O.F. Wet	Moisture Absorption	Breaking Strength	MOH's Rating	Chemical Resistance	Abrasion Resistance
<0.42	<20%	100-230 lbs	4.0-6.5	Resistant	N/A

COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
APPLICATION	Residential	Light Commercial	Commercial	Residential	Commercial
Floors / Patios (covered & uncovered)					
Walls / Backsplashes	X	X	X		
Countertops					
Pool Deckings					
Pool Linings			_		

RESIDENTIAL USAGE

APPLICATION				
Floors	Walls	Countertops	Exterior Patios	Exterior Pool Decks
	X			



- Suitable for exterior walls in non-freezing climates when proper installation methods are followed.
- Darker colors may show scratches.
- *The marketing name for this product is property of CobsA-USA. This same product may be marketed under different names.*