

SALERNO

porcelain collection



COBSA USA
NEW YORK | NEW JERSEY | MIAMI



BEIGE

DOMSABE1224



-12x24-

DOMSABE2448



-24x48-

DOMSABEMOSPAR



-parquet mosaic-

DOMSABESTICK



-stick mosaic-

DOMSABE2448STR



-24x48 structured-

DOMSABEBN324



-3x24 bullnose-



DOMSABI1224



-12x24-

DOMSABI2448



-24x48-

DOMSABIMOSPAR



-parquet mosaic-

DOMSABISTICK



-stick mosaic-

DOMSABI2448STR



-24x48 structured-

DOMSABIBN324



-3x24 bullnose-



DOMSAGR1224



-12x24-

DOMSAGR2448



-24x48-

DOMSAGRMOSPAR



-parquet mosaic-

DOMSAGRSTICK



-stick mosaic-

DOMSAGR2448STR



-24x48 structured-

DOMSAGRBN324



-3x24 bullnose-

Salerno



DOMSAVI1224



-12x24-

DOMSAVI2448




-24x48-

DOMSAVIMOSPAR



-parquet mosaic-

DOMSAVISTICK



-stick mosaic-

DOMSAVI2448STR



-24x48 structured-

DOMSAVIBN324



-3x24 bullnose-



Salerno



SALERNO COLLECTION

TILE

Type	Finish	Thickness	Edge	# Faces
Porcelain Glazed Color-Bodyed	Matte	9mm	Rectified	*See Below

*24x48: 16 faces, 24x48 structured: 1 face, 12x24: 64 faces

INSTALLATION

Grout Joint	Setting	Offset %	Shade Variation
1/16"			 V2 (Slight)

PERFORMANCE

	Test Method	Result
Water Absorption	ASTM C373	<0.5%
Breaking Strength	ASTM C648	≥35 N/mm ²
Scratch Hardness	MOHS	≥6
Wear Resistance	ANSI A137.1	Class 5
Slip Resistance	ASTM C1028	R10, Class B
Chemical Resistance	ASTM C650	Resistant
Stain Resistance	ASTM C1378	5
Thermal Shock Resistance	ASTM C484	Resistant
Freezing Resistance	ASTM C1026	Resistant

LEED CERTIFICATIONS

	Pts
Indoor Environmental Quality / Low-Emitting Materials	1
Materials and Sources / Sourcing of Raw Materials	1-3

APPLICATIONS

	Suitable	DCOF*
Dry & Level - Interior Floor	✓	N/A
Wet & Level - Interior Floor	✓	≥0.42
Shower Floors	✓	≥0.42
Exterior Floors (including patios, pool decking and other wet areas with minimal footwear)	✓	≥0.60
Ramps and Inclines	✓	≥0.65
Walls & Backsplashes	✓	
Countertops		
Pool Linings	✓	
Residential	✓	
Light Commercial	✓	
Heavy Commercial	✓	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3

NOTES

- Variations occur in all fired ceramic and natural tile products.
- Random visual variation enhances the natural beauty of this product.
- For optimal results:
 - Select tile from multiple cartons.
 - Plan shading and graphic arrangement prior to installation.
- Tile/trim supplied for a particular installation may not match samples exactly.
- Final confirmation of actual tiles and trim should be made prior to installation.
- Products are manufactured in accordance with ANSI A137.1 standards.
- Special care should be taken when grouting with dark pigmented colors.
- Use of a latex-modified thin-set is recommended for installation.